



Inkjet Technology, Inc.

ITI3200-TXR

Dual Production: Direct-to-Fabric and Transfer Paper Sublimation Printer



Production performance, direct to fabric and transfer paper.

Advanced print heads Ricoh Gen5 greyscale print head technology, variable drop size from 7-21 picoliters

High speed performance Printing speeds up to 1,300 sqft/hr in production quality mode utilizing an eight print head configuration

Super-wide format Maximum printing width of 10-feet (3.2 meters) for large textile display applications

High image quality Images at a resolution up to 605 x 1200 dpi in standard CMYK

Stable media handling Tension feeding system keeps fabric from buckling and transfer paper from cockling, no pinch rollers

Heated ink setting system Integrated infrared heater quickly sets ink before take-up

A multitude of applications Suitable for large run specialty fabrics, soft signage and fabric displays, flags and banners

Supported by ITI Standard one-year limited warranty



ITI3200-TXR Dual Production: Direct-to-Fabric & Transfer Paper Sublimation Printer

TECHNICAL SPECIFICATIONS

| PRINT | |
|---|---|
| Print head | 4 to 8 Ricoh Gen 5 |
| Print modes | Production Quality: 1300 sqft/hr (120.7 sqm/hr) 2 pass |
| | Standard Quality: 970 sqft/hr (90 sqm/hr) 3 pass |
| | High Quality: 700 sqft/hr (65 sqm/hr) 4 pass |
| Print resolution | Up to 605 x 1200 dpi |
| Technology | Piezo-electric inkjet; Greyscale |
| Ink type | Dye sublimation |
| Ink color | C M Y K |
| Ink reservoir size | 2.5 liter max. capacity (1 liter ink bottles to refill) |
| RIP software compatibility | PhotoPRINT, Caldera 10, Onyx other drivers available |
| Color management | ICC based color, adjustment curves, density adjustment |
| File formats | TIFF, JPEG, PS, EPS, PDF |
| MEDIA | |
| Media handling | Roll feed |
| Media types | Polyester fabric, blended fabric, blackout fabric |
| | Transfer paper from 58 - 140 gsm capability |
| Media width (max) | 128" |
| Media roll weight (max) | 220 lb. |
| Media roll diameter (max) | 16" |
| Media feeding | Adjustable tension system |
| Media heaters | In-line dual infrared heaters in front |
| OPERATION | |
| Standard interface | USB |
| Maximum power | Printer: 950 watts Heater/Dryer: 10kw |
| Power requirements | Printer: 220VAC, single-phase, 50/60 Hz, 16A |
| | Heater/Dryer: 220VAC, single-phase, 50/60 Hz, 46A |
| Temperature | 68°F to 86°F |
| Relative humidity | 35% to 65%, non-condensing |
| DIMENSIONS & WEIGHT | |
| Printer dimensions | 205.9"L x 73.5"W x 67.7"H |
| Shipping dimensions | 226"L x 82.7"W x 82.7"H |
| Weight | 2400 lbs. |
| WARRANTY | |
| One Year Limited Warranty (Please consult your dealer for Warranty details) | |

Specifications and terms are subjects to change without notice. ITI is a trademark of Inkjet Technology, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Copyright 2016 Inkjet Technology, Inc.

ITI3200-TXR 0716 rev 1.0